

CORRECTED VERSION

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
22 January 2004 (22.01.2004)

PCT

(10) International Publication Number  
WO 2004/007114 A1

- (51) International Patent Classification<sup>7</sup>: B22D 11/06
- (21) International Application Number:  
PCT/EP2003/007484
- (22) International Filing Date: 10 July 2003 (10.07.2003)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:  
MI2002A001505 10 July 2002 (10.07.2002) IT
- (71) Applicant (for all designated States except US): DANIELI  
& C. OFFICINE MECCANICHE S. P. A. [IT/IT]; Via  
Nazionale, 41, I-33042 Buttrio (IT).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): BOTHAM, Brian,


W. [GB/GB]; The Croft, 1103, Town Street, Lound,  
Retford, Nottinghamshire DN 228SA (GB). DE LUCA,  
Andrea [IT/IT]; Via Malignani, 13/6, 33047 Reman-  
zacco (IT). POLONI, Alfredo [IT/IT]; Via G. Paolini,  
29, I-34070 Fogliano Redipuglia (IT). FAGGIANI, Edi  
[IT/IT]; Piazzale Cavedalis, 6/2, I-33100 Udine (IT).  
KAPAJ, Nuredin [AL/IT]; Via Caprera, 7, I-33100 Udine  
(IT).

(74) Agent: GERVASI, Gemma; Notarbartolo & Gervasi  
S.P.A., Corso di Porta Vittoria, 9, I-20122 Milano (IT).

(81) Designated States (national): AE, AG, AL, AM, AT, AU,  
AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU,  
CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH,  
GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC,  
LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW,  
MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC,

[Continued on next page]

(54) Title: ROLL SUPPORT DEVICE FOR CONTINUOUS METALLIC STRIP CASTING



(57) Abstract: Support device for an assembly (14) of the casting rolls (11, 11') of a continuous metallic strip casting line comprising a movable support at each axial end. Such supports (17, 17', 19, 19') are provided with a hydraulic bearing (13) to reduce friction during motion with respect to the assembly. Between the movable supports of one of the rolls (11) and the assembly is located a hydraulic actuator (18), which thrusts the first roll (11') towards the second roll (11') against a stop (16). Between the second roll (11') and the assembly there are located magnetostrictive actuators which thrust the second roll (11') against the first roll (11). The device has a joint provided with a housing (22) inside which a telescopic tube (21) for the supply of the cooling water to conduits present in the rolls may slide. The housing (22) is connected to the assembly (14) by means of a bellows (27) allowing for oscillation.

WO 2004/007114 A1



SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA,  
UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

**Published:**

— with international search report

(84) **Designated States (regional):** ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

(48) **Date of publication of this corrected version:**

15 April 2004

(15) **Information about Correction:**

see PCT Gazette No. 16/2004 of 15 April 2004, Section II

**Declaration under Rule 4.17:**

— of inventorship (Rule 4.17(iv)) for US only

*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*